

Amendments to the Claims

This listing of claims replaces all prior versions and listings of claims:

Listing of Claims:

1. (Currently amended) A motorcycle comprising:

a body frame;

a seat fixed to the body frame;

a seat cowl provided separately from and rearwardly of a the seat; and

a pair of left and right glove bars provided in the vicinity of a rear portion of the seat, and wherein

rear portions of the glove bars and the seat cowl are formed integrally, and

front and rear portions of the glove bars, respectively, are mounted to a the body frame.

2. (Currently amended) ~~The A motorcycle according to claim 1, further comprising:~~

a seat cowl provided rearwardly of a seat;

a pair of left and right glove bars provided in the vicinity of a rear portion of the seat, wherein rear portions of the glove bars and the seat cowl are formed integrally, and front and rear portions of the glove bars, respectively, are mounted to a body frame;

a front mount, by which the front portions of the glove bars are mounted to a vehicle body from laterally a lateral direction, and

a rear mount, by which the rear portions of the glove bars are mounted to the vehicle body from above, and wherein

the glove bars are arranged so that at least the front portions thereof are inclined forward and downward as viewed in side view and the front mount is arranged on forward extensions of the front portions of the glove bars.

3. (Previously presented) The motorcycle according to claim 2, wherein the rear mount is covered by the seat from above.

4. (Original) The motorcycle according to claim 1, wherein both side walls of the seat cowl in a left and right direction are formed curvedly to be made convex outside the vehicle body as viewed from the rear of the vehicle body.

5. (Original) The motorcycle according to claim 4, further comprising a reinforcement rib provided on an inner surface of a side wall of the seat cowl to extend vertically.

6. (Previously presented) A motorcycle comprising:
a seat cowl provided rearwardly of a seat;
a pair of left and right glove bars provided in the vicinity of a rear portion of the seat, wherein
rear portions of the glove bars and the seat cowl are formed integrally,
front and rear portions of the glove bars, respectively, are mounted to a body frame, and

both side walls of the seat cowl in a left and right direction are formed curvedly to be made convex outside the vehicle body as viewed from the rear of the vehicle body;

a reinforcement rib provided on an inner surface of a side wall of the seat cowl to extend vertically; and

a tail light mounted to the reinforcement rib.

7. (Currently amended) The motorcycle according to claim 5, wherein the reinforcement rib is provided in the vicinity of the a rear mount by which the rear portions of the glove bars are mounted to a vehicle body from above.

8. (Currently amended) The motorcycle according to any one of claims ~~1 to 7~~ 2, 3 or 6, wherein the glove bars and the seat cowl are molded from a reinforced ~~plastics~~ plastic with glass fibers.

9. (New) The motorcycle according to any one of claims 1, 4, 5 or 7, wherein the glove bars and the seat cowl are molded from a reinforced plastic with glass fibers.